



# Mark Scheme (Results)

Summer 2025

Pearson Edexcel International Advanced  
Subsidiary Level in Physics (WPH11)  
Paper 01 Mechanics and Materials

## **Edexcel and BTEC Qualifications**

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at [www.edexcel.com](http://www.edexcel.com) or [www.btec.co.uk](http://www.btec.co.uk). Alternatively, you can get in touch with us using the details on our contact us page at [www.edexcel.com/contactus](http://www.edexcel.com/contactus).

## **Pearson: helping people progress, everywhere**

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: [www.pearson.com/uk](http://www.pearson.com/uk)

Summer 2025

Question Paper Log Number P78753A

Publications Code WPH11\_01\_2506\_MS

All the material in this publication is copyright

© Pearson Education Ltd 2025

## General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

## Mark Scheme Notes:

This mark scheme is published to help teachers and candidates understand the exam requirements. Please note that the mark schemes can be better understood when viewed alongside the question paper and the Principal Examiner Report for Teachers.

It's important to emphasise that a mark scheme is a work in progress that can be further refined and expanded based on students' responses to a particular paper.

It is important to avoid making assumptions about future mark schemes based on a document from one year.

Although the guiding principles of assessment remain constant, the details may vary based on the content of a particular examination paper.

## Underlying principle

The mark scheme will clearly indicate the concept that is being rewarded, backed up by examples. **It is not a set of model answers.**

### 1. Mark scheme format

- 1.1 You will not see 'wtte' (words to that effect). Alternative correct wording should be credited in every answer unless the MS has specified specific words that must be present. Such words will be indicated by underlining e.g. 'resonance'
- 1.2 Bold lower case will be used for emphasis e.g. '**and**' when two pieces of information are needed for 1 mark.
- 1.3 Round brackets ( ) indicate words that are not essential e.g. "(hence) distance is increased".
- 1.4 Square brackets [ ] indicate advice to examiners or examples e.g. [Do not accept gravity] [ecf].

### 2. Unit error penalties

- 2.1 A separate mark is not usually given for a unit but a missing or incorrect unit will normally mean that the final calculation mark will not be awarded.
- 2.2 This does not apply in 'show that' questions or in any other question where the units to be used have been given, for example in a spreadsheet.
- 2.3 The mark will not be awarded for the same missing or incorrect unit only once within one clip in epen.
- 2.4 Occasionally, it may be decided not to insist on a unit e.g. the candidate may be calculating the gradient of a graph, resulting in a unit that is not one that should be known and is complex.
- 2.5 The mark scheme will indicate if no unit error is to be applied by placing brackets around the unit.

### 3. Significant figures

- 3.1 Use of too many significant figures in the theory questions will not prevent a mark being awarded if the answer given rounds to the answer in the MS.
- 3.2 Too few significant figures will mean that the final mark cannot be awarded in 'show that' questions where one more significant figure than the value in the question is needed for the candidate to demonstrate the validity of the given answer.
- 3.3 The use of one significant figure might be inappropriate in the context of the question e.g. reading a value off a graph. If this is the case, there will be a clear indication in the MS.
- 3.4 The use of  $g = 10 \text{ m s}^{-2}$  or  $10 \text{ N kg}^{-1}$  instead of  $9.81 \text{ m s}^{-2}$  or  $9.81 \text{ N kg}^{-1}$  will be penalised by one mark (but not more than once per clip). Accept  $9.8 \text{ m s}^{-2}$  or  $9.8 \text{ N kg}^{-1}$
- 3.5 In questions assessing practical skills, a specific number of significant figures will be required e.g. determining a constant from the gradient of a graph or in uncertainty calculations. The MS will clearly identify the number of significant figures required.

### 4. Calculations

- 4.1 **use of** the formula means that the candidate demonstrates substitution of physically correct values, although there may be conversion errors e.g. power of 10 error.
- 4.2 If a 'show that' question is worth 2 marks, then both marks will be available for a reverse working. If the question is worth 3 marks then only 2 marks will be available.
- 4.3 The mark scheme will show a correctly worked answer for illustration only.

### 5. Quality of Written Expression

- 5.1 Questions that assess the ability to show a coherent and logically structured answer are marked with an asterisk.
- 5.2 Marks are awarded for indicative content and for how the answer is structured.
- 5.3 Linkage between ideas, and fully-sustained reasoning is expected.

| Question Number | Answer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Mark |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 1               | <p><b>The only correct answer is D (<math>W</math>)</b></p> <p>A is not correct because upthrust is equal to the weight of liquid displaced<br/> B is not correct because upthrust is equal to the weight of liquid displaced<br/> C is not correct because upthrust is equal to the weight of liquid displaced</p>                                                                                                                                                                            | 1    |
| 2               | <p><b>The only correct answer is A (The resultant force is zero and the resultant moment is zero)</b></p> <p>B is not correct because the resultant moment should be zero<br/> C is not correct because the resultant force should be zero<br/> D is not correct because the resultant force should be zero and the resultant moment should be zero</p>                                                                                                                                        | 1    |
| 3               | <p><b>The only correct answer is B (<math>t</math>)</b></p> <p>A is not correct because the vertical acceleration is the same for both balls and vertical motion is independent of horizontal motion<br/> C is not correct because the vertical acceleration is the same for both balls and vertical motion is independent of horizontal motion<br/> D is not correct because the vertical acceleration is the same for both balls and vertical motion is independent of horizontal motion</p> | 1    |
| 4               | <p><b>The only correct answer is C (The forces act on the same object.)</b></p> <p>A is not correct because the motion of the chair is not relevant<br/> B is not correct because forces forming a Newtons' third law pair act in opposite directions<br/> D is not correct because forces forming a Newtons' third law pair have the same magnitude</p>                                                                                                                                       | 1    |
| 5               | <p><b>The only correct answer is B (<math>\vec{W} + \vec{T}_1 + \vec{T}_2 = 0</math>)</b></p> <p>A is not correct because the vector sum of <math>T_1 + T_2</math> is in the opposite direction to <math>W</math><br/> C is not correct because <math>T_2</math> should not be subtracted from <math>T_1</math><br/> D is not correct because <math>T_2</math> should not be subtracted from <math>T_1</math></p>                                                                              | 1    |
| 6               | <p><b>The only correct answer is B (parabola-shaped graph)</b></p> <p>A is not correct because the acceleration is zero<br/> C is not correct because the acceleration is zero<br/> D is not correct because the acceleration is zero where the line is straight, acceleration changes where the line curves, and acceleration is zero again when the line becomes straight again.</p>                                                                                                         | 1    |
| 7               | <p><b>The only correct answer is D (<math>\sqrt{(15\,000 - 14\,500)^2 + 200^2}</math>)</b></p> <p>A is not correct because the answer should be square rooted and the resultant of the vertical forces should be determined before squaring<br/> B is not correct because the resultant of the vertical forces should be determined before squaring<br/> C is not correct because the answer should be square rooted</p>                                                                       | 1    |

|    |                                                                                                                                                                                                                                                                                                                                                                    |   |
|----|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|
| 8  | <p><b>The only correct answer is C (<math>F = W\sin\theta</math>)</b></p> <p>A is not correct because <math>W \cos \theta</math> is perpendicular to the slope<br/>         B is not correct because <math>W \cos \theta</math> is perpendicular to the slope<br/>         D is not correct because the resultant force must be zero</p>                           | 1 |
| 9  | <p><b>The only correct answer is A (<math>\frac{50 \times 10^3 \times 2.3}{13}</math>)</b></p> <p>B is not correct because work done should be power <math>\times</math> time<br/>         C is not correct because the answer is inverted<br/>         D is not correct because work done should be power <math>\times</math> time and the answer is inverted</p> | 1 |
| 10 | <p><b>The only correct answer is A (<math>\frac{v}{4}</math>)</b></p> <p>B is not correct because conserving momentum does not lead to this answer<br/>         C is not correct because the new speed is not just the difference between the initial speeds<br/>         D is not correct because the initial velocities are in opposite directions</p>           | 1 |

| Question Number | Acceptable Answer                                                                                    | Additional Guidance                                                                                                                                                               | Mark |
|-----------------|------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 11              | Use of $F = ma$ with $F = 4800 \text{ N}$ (1)<br>Use of $W = mg$ (1)<br>$W = 150\,000 \text{ N}$ (1) | <u>Example calculation</u><br>$m = \frac{4800 \text{ N}}{0.31 \text{ m s}^{-2}} = 15\,500 \text{ kg}$ $W = 15\,500 \text{ kg} \times 9.81 \text{ N kg}^{-1} = 152\,000 \text{ N}$ | 3    |

(Total for Question 11 = 3 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                      | Additional Guidance                                                                                                                                                                                                                                                                                                          | Mark |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 12(a)           | <p>Displacement is a straight line (from start to end) (1)</p> <p>(Whereas) distance is the length of the path (1)</p>                                                                                                 | <p>Allow (whereas) distance is not a straight line<br/> Allow the person does not travel in a straight line<br/> Allow the path is not a straight line</p> <p>If no other mark scored allow 1 mark for 'displacement is a vector but distance is a scalar'</p>                                                               | 2    |
| 12(b)           | <p>Two pairs of corresponding values of velocity and time read from graph (1)</p> <p>Calculates gradient of the line between 4 s and 16 s (1)</p> <p>Maximum acceleration = <math>0.27 \text{ m s}^{-2}</math> (1)</p> | <p>No tolerance if readings taken at 4 s and 16 s<br/> Allow a tolerance of <math>\pm \frac{1}{2}</math> a small square if readings taken from other points on the graph</p> <p><u>Example calculation</u></p> $a = \frac{5.0 \text{ m s}^{-1} - 1.8 \text{ m s}^{-1}}{16 \text{ s} - 4 \text{ s}} = 0.267 \text{ m s}^{-2}$ | 3    |

(Total for Question 12 = 5 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Additional Guidance                                                                                                                                                                                                                                                                                                                                                 | Mark |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 13              | <p>Use of <math>v^2 = u^2 + 2a\Delta s</math> (1)</p> <p><math>\Delta s = 1.1 \text{ m}</math> (1)</p> <p>Comparison of <math>(1.7 + \text{their calculated } \Delta s)</math> with <math>3.0 \text{ m}</math> and consistent conclusion</p> <p><b>Or</b></p> <p>Comparison of their calculated <math>\Delta s</math> with <math>1.3 \text{ m}</math> and consistent conclusion</p> <p><b>Or</b></p> <p>Comparison of <math>(3.0 - \text{their calculated } \Delta s)</math> with <math>1.7 \text{ m}</math> and consistent conclusion (1)</p> | <p>allow use of any valid suvat method to determine <math>\Delta s</math></p> <p><u>Example calculation</u></p> $\Delta s = \frac{(-2.1 \text{ m s}^{-1})^2 - (5.1 \text{ m s}^{-1})^2}{2 \times (-9.81 \text{ m s}^{-2})} = 1.1 \text{ m}$ <p><math>s = 1.7 \text{ m} + 1.1 \text{ m} = 2.8 \text{ m}</math></p> <p><math>2.8 \neq 3.0 \text{ m}</math>, so no</p> | 3    |

(Total for Question 13 = 3 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                                                              | Additional Guidance                                                                                                                                                                                                                                                                                                                                                                                             | Mark |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 14              | <p>Use of <math>E_k = \frac{1}{2}mv^2</math> (1)</p> <p>Use of <math>\Delta E_{\text{grav}} = mg\Delta h</math> (1)</p> <p>Use of efficiency = <math>\frac{\text{useful energy output}}{\text{total energy input}}</math> (1)</p> <p>Efficiency = 0.28 (1)</p> | <p>Allow efficiency = 28% (must include % symbol)</p> <p><u>Example calculation</u></p> $E_k = \frac{1}{2} \times 1800 \text{ kg} \times (14 \text{ m s}^{-1})^2 = 176\,000 \text{ J}$ $\Delta E_{\text{grav}} = 1800 \text{ kg} \times 9.81 \text{ N kg}^{-1} \times 0.76 \text{ m} = 13\,400 \text{ J}$ $\text{Efficiency} = \frac{45 \times 10^3 \text{ J}}{176\,000 \text{ J} - 13\,400 \text{ J}} = 0.277$ | 4    |

(Total for Question 14 = 4 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                                                                                                                             | Additional Guidance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Mark |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 15(a)           | <p>Compression changes from 60 nm to 97.5 nm</p> <p>Use of <math>E_{el} = \frac{1}{2}F\Delta x</math> with corresponding values of <math>F</math> and compression</p> <p><b>or</b></p> <p>Determines area under graph between 85 N and 140 N</p> <p>Increase in elastic strain energy = <math>4.3 \times 10^{-6}</math> J</p> | <p>(1) Allow compression changes from a value between 55 nm and 62 nm to a value between 95 nm and 100nm</p> <p>(1)</p> <p>(1) Allow an answer consistent with their allowed readings from the graph.</p> <p><u>Example calculation</u></p> $E_{el} = \frac{1}{2} 140 \text{ N} \times 97.5 \times 10^{-9} \text{ m} = 6.83 \times 10^{-6} \text{ J}$ $E_{el} = \frac{1}{2} 85 \text{ N} \times 60 \times 10^{-9} \text{ m} = 2.55 \times 10^{-6} \text{ J}$ $\Delta E_{el} = 6.83 \times 10^{-6} \text{ J} - 2.55 \times 10^{-6} \text{ J} = 4.28 \times 10^{-6} \text{ J}$ | 3    |
| 15(b)           | <p>(The brick) returns to its original size / shape / length when the force / stress is removed</p>                                                                                                                                                                                                                           | (1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 1    |

(Total for Question 15 = 4 marks)

| Question Number | Acceptable Answer                                                                                                                                                                     |                           | Additional Guidance                                                                                                                                                                                                                                                     | Mark |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 16(a)           | Mass of the ball-bearing                                                                                                                                                              | (1)                       | Allow weight of ball-bearing<br>Allow mass / weight of (a known volume of) oil<br>Allow volume of (a known mass of) oil<br>Allow density of oil<br><br>Ignore radius / diameter / volume of ball-bearing<br>Ignore density of ball-bearing<br>Ignore temperature of oil | 1    |
| 16(b)           | Use of $s = ut + \frac{1}{2}at^2$ with $a = 0$<br><br>Use of $F = 6\pi\eta rv$<br><br>$\eta = 0.031 \text{ (Pa s)}$                                                                   | (1)<br><br>(1)<br><br>(1) | <u>Example calculation</u><br><br>$v = \frac{0.20 \text{ m}}{1.3 \text{ s}} = 0.154 \text{ m s}^{-1}$ $\eta = \frac{5.6 \times 10^{-5} \text{ N}}{6 \times \pi \times \frac{1.24 \times 10^{-3}}{2} \times 0.154 \text{ m s}^{-1}} = 0.0311 \text{ Pa s}$               | 3    |
| 16(c)           | (At a lower temperature) the oil has a greater viscosity<br><br>(So) the ball falls at a smaller (terminal) velocity<br><br>(So) time taken is greater (for the ball to fall 20.0 cm) | (1)<br><br>(1)<br><br>(1) | MP3 dependent on MP1 or MP2                                                                                                                                                                                                                                             | 3    |

(Total for Question 16 = 7 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                                                                                  | Additional Guidance                                                                                                                                                                                                                                                                                                                                                    | Mark |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 17(a)           | <p>Corresponding force and extension read from graph (1)</p> <p>Use of <math>\Delta F = k\Delta x</math> (1)</p> <p><math>k = 2760 \text{ N m}^{-1}</math> (1)</p> <p>Comparison with 2700 (<math>\text{N m}^{-1}</math>) and consistent conclusion (1)</p>                        | <p>Allow a tolerance of <math>\pm \frac{1}{2}</math> a small square</p> <p>Allow a value of <math>k</math> between 2650 and 2850</p> <p><u>Example calculation</u></p> $k = \frac{80 \text{ N}}{29 \times 10^{-3} \text{ m}} = 2760 \text{ N m}^{-1}$ <p><math>2760 \text{ N m}^{-1} \approx 2700 \text{ N m}^{-1}</math> so this is string Y</p>                      | 4    |
| 17(b)           | <p>Calculates cross-sectional area of string (1)</p> <p>Use of <math>\sigma = \frac{F}{A}</math> (1)</p> <p>Use of <math>\varepsilon = \frac{\Delta x}{x}</math> (1)</p> <p>Use of <math>E = \frac{\sigma}{\varepsilon}</math> (1)</p> <p><math>E = 6.0 \text{ GPa}</math> (1)</p> | <p><u>Example calculation</u></p> $A = \pi \times (0.85 \times 10^{-3} \text{ m})^2 = 2.27 \times 10^{-6} \text{ m}^2$ $\sigma = \frac{36 \text{ N}}{2.27 \times 10^{-6} \text{ m}^2} = 15.9 \times 10^6 \text{ Pa}$ $\varepsilon = \frac{0.002 \text{ m}}{0.750 \text{ m}} = 0.00267$ $E = \frac{15.9 \times 10^6 \text{ Pa}}{0.00267} = 5.96 \times 10^9 \text{ Pa}$ | 5    |

(Total for Question 17 = 9 marks)


| Question Number | Acceptable Answer                                                                                 | Additional Guidance                                                                                                                                                                                                                                          | Mark |
|-----------------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 18(a)           | Calculates volume of sphere<br>Use of $\rho = \frac{m}{V}$<br>$m = 1.1 \times 10^{-2} \text{ kg}$ | (1)<br>(1)<br>(1)<br><u>Example calculation</u><br>$V = \frac{4}{3}\pi(7.0 \times 10^{-3} \text{ m})^3 = 1.44 \times 10^{-6} \text{ m}^3$<br>$m = 7.8 \times 10^3 \text{ kg m}^{-3} \times 1.44 \times 10^{-6} \text{ m}^3 = 1.12 \times 10^{-2} \text{ kg}$ | 3    |
| 18(b)           | Use of appropriate trigonometry<br>Initial acceleration = $6.0 \text{ m s}^{-2}$                  | (1)<br>(1)<br><u>Example calculation</u><br>Resultant force = $m \times 9.81 \text{ m s}^{-2} \times \sin(38^\circ)$<br>= $m \times 6.04 \text{ m s}^{-2}$<br>$F = ma$ , so $a = 6.04 \text{ m s}^{-2}$                                                      | 2    |



| Question Number | Acceptable Answer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Additional Guidance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Mark     |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| 19(a)           | <p>Total clockwise moment = total anticlockwise moment<br/> <b>Or</b><br/> Resultant moment = zero<br/> <b>Or</b><br/> Sum of all moments = zero</p> <p style="text-align: right;"><b>(1)</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | <b>1</b> |
| 19(b)(i)        | <p>Use of trigonometry to determine appropriate component of piston force<br/> <b>Or</b><br/> Use of trigonometry to determine perpendicular distance from pivot to line of action of piston force</p> <p style="text-align: right;"><b>(1)</b></p> <p>Use of trigonometry to determine appropriate component of weight<br/> <b>Or</b><br/> Use of trigonometry to determine perpendicular distance from pivot to line of action of weight</p> <p style="text-align: right;"><b>(1)</b></p> <p>Use of moment = <math>Fx</math></p> <p style="text-align: right;"><b>(1)</b></p> <p>Use of principle of moments</p> <p style="text-align: right;"><b>(1)</b></p> <p>Minimum force = 22 N</p> <p style="text-align: right;"><b>(1)</b></p> | <p><u>Example calculation</u></p> <p>Moment of <math>F_{\text{piston}}</math> about pivot = <math>160 \text{ N} \times \sin 18^\circ \times 0.37 \text{ m}</math><br/> = 18.3 Nm</p> <p>Moment of weight about pivot = <math>95 \text{ N} \times \cos 42^\circ \times 0.70 \text{ m}</math><br/> = 49.4 Nm</p> <p><math>18.3 \text{ Nm} + F \times 1.40 \text{ m} = 49.4 \text{ Nm}</math></p> <p><math>F = \frac{49.4 \text{ N m} - 18.3 \text{ N m}}{1.40 \text{ m}} = 22.2 \text{ N}</math></p> | <b>5</b> |

|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                             |   |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---|
| 19(b)(ii) | <p>(each force applied by the student must cause) the same moment (about the pivot) (1)</p> <p>(When the force is vertical) The component of the force perpendicular to the rail must be the same</p> <p><b>Or</b></p> <p>(When the force is vertical) The perpendicular distance from the (line of action of the) force to the pivot is less</p> <p><b>Or</b></p> <p>If the same (magnitude) force is applied vertically, the moment of the force (about the pivot) is less (1)</p> <p>(So when the force is vertical) the force needed is greater (1)</p> | MP3 dependent on MP1 or MP2 | 3 |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|---|

(Total for Question 19 = 9 marks)

| Question Number | Acceptable Answer                                                                                                                                                                                                                                                                                  |                                             | Additional Guidance                                                                                                                                                                                                                                                                                                                                                                                      | Mark |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 20(a)           | <p>Use of <math>s = ut + \frac{1}{2}at^2</math> with <math>u = 0</math></p> <p><math>a = 9.78 \text{ m s}^{-2}</math></p> <p>Determines an appropriate proportion of <math>g</math></p> <p>Comparison of calculated value of <math>a</math> with <math>0.95 g</math> and consistent conclusion</p> | <p>(1)</p> <p>(1)</p> <p>(1)</p> <p>(1)</p> | <p>allow use of any valid suvat method to determine <math>a</math></p> <p>MP4 dependent on MP3</p> <p><u>Example calculation</u></p> $11 = (0.0 \times 1.5) + \frac{1}{2} a \times 1.5^2$ $a = \frac{2 \times 11 \text{ m}}{(1.5 \text{ s})^2} = 9.78 \text{ m s}^{-2}$ $\frac{9.78 \text{ m s}^{-2}}{9.81 \text{ m s}^{-2}} = 0.997$ <p>0.997 is greater than 0.95 so air resistance was negligible</p> | 4    |
| 20(b)           | <p>Curved line starting at zero with negative gradient decreasing in magnitude</p> <p>Horizontal line after 12 seconds</p>                                                                                                                                                                         | <p>(1)</p> <p>(1)</p>                       | <p>ignore any values added to the y-axis</p> <p>Line should not be along the x-axis</p> <p><u>Example graph:</u></p>                                                                                                                                                                                                | 2    |

|              |                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                                                                                  |          |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| <b>20(c)</b> | $E_{\text{grav}}$ decreases (throughout) (1)<br>While accelerating, $E_k$ increases (1)<br>and work is done against air resistance<br><b>or</b><br>and energy is dissipated due to (work done against) air resistance (1)<br><br>At terminal velocity ( $E_k$ is constant and) all $\Delta E_{\text{grav}}$ is dissipated (due to work done against air resistance) (1)                                                                    | Ignore references to heating<br>Ignore references to thermal energy<br>Allow energy is transferred to the surroundings due to (work done against) air resistance | <b>4</b> |
| <b>20(d)</b> | (When the parachute opens,) air resistance is greater than weight (1)<br><br>(So) resultant force is upwards and acceleration is upwards<br><b>or</b><br>(so) resultant force is upwards and the skydiver decelerates (1)<br><br>(As speed decreases) air resistance decreases (so acceleration/deceleration decreases) (1)<br><br>(Until upthrust +) air resistance = weight (1)<br><br>(so) resultant force = 0 and acceleration = 0 (1) | Allow drag for air resistance throughout<br><br>Ignore speed decreases<br><br><br><br>Ignore speed is constant                                                   | <b>5</b> |

(Total for Question 20 = 15 marks)  
**TOTAL FOR PAPER = 80 MARKS**

